



## M/V 'SLOMAN DISPATCHER'

Valid as of 09 May 2025

<b>Registration</b>	V2FO3	TEU slots for IMO class 1	Class 1.1 -1.6 on all deck and hold #1. Class 1.4S all deck and holds
Call sign	9620657	<b>Deck loads</b>	
IMO number	St. John's	Tanktop	16,0 mt/m <sup>2</sup>
Port of registry	Antigua & Barbuda	T/D #1 and # 2 upper	2,5 mt/m <sup>2</sup>
Flag state	Jiangzhou Shipyards	T/D #2 mid/low and #3	4,0 mt/m <sup>2</sup>
Shipyards	2012/Ruichang - China	Hatch covers (HC)	1,75 mt/m <sup>2</sup>
Year/Place of delivery	DNV-GL	<b>Hatch cover/Tween deck</b>	
Class	☑ 100 A5 E3 Multi-purpose dry cargo ship BWM Equipp. for carr. of contr. DBC SOLAS-II-2, Reg.19 ERS G IW Strength. For heavy cargo	Type of hatch covers	Hydraulic folding
Class notation	☒ MC E3 AUT	Tween deck pontoons	14 removable pontoons Adjustable in three position in hold #2 (can be used as bulkheads)
P&I Club	Steamship Mutual	<b>Propulsion/Manoeuvring</b>	
<b>Tonnage</b>		Main Engine	5.400 kW
DWAT	12.204 mt (incl. tween decks)	Bow thruster	500 kW
DWCC	Abt. 11.200 mt	Shaft generator	700 kW
Gross tonnage	9611	Propeller	Controllable pitch propeller
Net tonnage	4260	Rudder	Free-hanging flap type
		Service speed	14,0 kn
<b>Dimensions</b>		<b>Bunkers/Ballast capacity</b>	
Length over all	138,01 m	Heavy fuel oil	Abt. 760 m <sup>3</sup>
Length between p.p.	130,00 m	Marine gas oil	Abt. 337 m <sup>3</sup>
Breadth over all	21,00 m	Lubricating oil	Abt. 50 m <sup>3</sup>
Breadth moulded	21,00 m	Fresh water	Abt. 120 m <sup>3</sup>
Summer draught	8,00 m	Ballast water	Abt. 5000 m <sup>3</sup>
Depth moulded	11,00 m	<b>Cargo gear</b>	
Height keel to top mast	39,40 m	Cranes on port side	2 x NMF 150 mt SWL
<b>Hold/hatch sizes</b>		Load/Outreach	150 mt/4,5-16,0 m 120 mt/4,5-19,0 m 95 mt/4,0-24,0 m 70 mt/3,5-33,0 m
Number of holds/hatches	3/3	Tandem operation	300 mt SWL
Hold capacities	About 14.856 m <sup>3</sup> /524.634 ft <sup>3</sup>	Lifting beam on board	2 each 5,2 m and 8,2 m WLL 165 mt
#1 Hatch cover/opening	19,30 x 15,42/18,75 x 15,00m	<b>Lifting heights</b>	
#1 Tween deck	18,75 x 15,01/10,06 over 6 m	At 4,5 m outreach	34,6 m
#1 Hold	18,75 x 15,01/10,06 over 6 m	At 16,0 m outreach	31,6 m
#2 Hatch cover/opening	42,33 x 17,98/42,00 x 17,50m	At 19,0 m outreach	26,7 m
#2 Tween deck	42,00 x 17,50 m	At 24,0 m outreach	26,8 m
#2 Hold	42,00 x 17,50 m	At 33,0 m outreach	9,8 m
#3 Hatch cover/opening	26,00 x 17,98/25,50 x 17,50m		
#3 Tween deck	25,50 x 17,50 m		
#3 Hold	25,50 x 17,50/14,40 over 5 m		
Height T/T > H/C #1/#2/3	10,53/11,18/10,77 m		
Height T/T > T/D #1/#2/#3	5,43/3,25-7,45/5,59 m		
Height T/D > H/C #1/#2/#3	4,50/2,93-7,13/4,38 m		
Hatch cover surface	1.462 m <sup>2</sup>		
Tween deck surface	1.424 m <sup>2</sup>		
Lower hold surface	1.420 m <sup>2</sup>		
<b>Container capacity</b>			
Hold capacity	326 TEU		
Deck capacity	331 TEU (5+10+10 Reefer)		
Total	657 TEU (516 TEU @ 14 mt)		
Stack weight TEU/FEU	Tank top: 90/120 mt Hatch cover: 50/65 mt Deck: 35 mt/-		

*All details are believed to be correct but without guarantee/hws.*

Phone: +45 7070 1311  
E-mail: europe@ocean7projects.com  
Web: ocean7.com

